



# LCD MODULE SPECIFICATION

**Customer:** \_\_\_\_\_

**Model Name:** HC070IK28026-B62

**Date:** 2019/10/26

**Version:** 01

**Preliminary Specification**

**Final Specification**

## For Customer's Acceptance

Approved by	Comment

Approved by	Reviewed by	Prepared by

## **REVISION RECORD**

# 1.0 General description

## 1.1 Introduction

HC070IK28026-B62 is model a color active matrix thin film transistor (TFT) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching device. This model is composed of a TFT LCD panel, a driving circuit and a back light system. This TFT LCD has a **7.0 inch** diagonally measured active display area with **WSVGA (1024 horizontal by 600 vertical pixel array)** resolution. The TFT-LCD panel used for this module is adapted for a low reflection and higher color type.

## 1.2 Features

- **4 lanes MIPI Interface**
- Low driving voltage and low power consumption
- ROHS Compliant

## 1.3 General information

Item	Specification	Unit	Remarks
Outline Dimension	163.8(H) x 97(V) x 2.6(body)	mm	Tolerance: $\pm 0.2\text{mm}$
Display area	154.215(W) x 85.92(H)	mm	
Number of Pixel	1024(H) x RGB x600(V)	pixels	
Pixel pitch	0.1506(H) x 0.1432(V)	mm	
Pixel arrangement	Pixels RGB stripe arrangement		
Display mode	Normally Black		
Surface treatment	Hard Coating,IPS		
Back-light	Single LED (Side-Light type)		

## 1.4 Mechanical Information

Item	Min.	Typ.	Max.	Unit
Module Size	Horizontal(H)	163.6	163.8	164.0 mm
	Vertical(V)	96.8	97.0	97.2 mm
	Depth(D)	2.4	2.6	2.8 mm

## 2.0 ABSOLUTE MAXIMUM RATINGS

### 2.1 Electrical Absolute Rating

#### 2.1.1 TFT LCD Module

Item	Specification	Unit
Outline Dimension	163.8(H) x 97(V) x 2.6(body)	mm
Display area	154.215(W) x 85.92(H)	mm
Number of Pixel	1024(H) x RGB x 600(V)	pixels
Pixel pitch	0.1506(H) x 0.1432(V)	mm
Pixel arrangement	Pixels RGB stripe arrangement	
Display mode	Normally Black	
Surface treatment	Hard Coating, IPS Film	
Weight	TBD (Typ.)	gram
Back-light	Single LED (Side-Light type)	
Power Consumption	B/L System	watt

#### 2.1.2 Back-Light Unit

Item	Symbol	Typ	MIN.	TYP.	MAX.	Unit	Note
Forward voltage	Vf	9.3	9.0	9.3	9.5	V	(1)(2)
Forward current	If	180	--	--	--	mA	(1)(2)(3)
Power Consumption	PBL	--	--	--	--	mW	

Note:

- (1) Permanent damage may occur to the LCD module if beyond this specification. Functional operation should be restricted to the conditions described under normal operating conditions.
- (2)  $T_a = 25 \pm 2^\circ C$
- (3) Test Condition: LED current 180 mA

## 3.0 OPTICAL CHARACTERISTICS

### 3.1 Optical Specifications

Item	Symbol	Temp	Condition	Min	Typ	Max	Unit	Remark
Viewing Angle range	Horizontal	$\theta$	CR > 10	80	85	--	Deg	Note 1
	Vertical	$\theta$		80	85	--	Deg	
Luminance Contrast ratio	CR	$\theta = 0^\circ$	600: 1	800	--	--	--	Note 2
Brightness	YL			260	280	--	Cd/cm <sup>2</sup>	
Transmittance	T(%)	$\theta = 0^\circ$		5.0	--	--	%	Note 3
Color Gamut (C light)				45	50	--	%	
White chromaticity	Wx		$\Theta=0^\circ$	0.303				
	Wy			0.333				
Reproduction of color (C-light)	Red	Rx	$\Theta=0^\circ$	0.618	TYP. -0.02	TYP. +0.02		Note 4
		Ry		0.326				
	Green	Gx		0.285				
		Gy		0.539				
	Blue	Bx		0.146				
		By		0.148				
Response Time (Rising + Falling)	Trt		Ta= 25°C $\theta = 0^\circ$	--	25	40	ms	Note 5

### 3.2 Measuring Condition


Measuring surrounding: dark room ,LED current IL : 180mA

Ambient temperature: 25±2°C 15min. warm-up time.

### 3.3 Measuring Equipment

FPM520 of Westar Display technologies, INC., which utilized SR-3 for Chromaticity and BM-5A for other optical characteristics. Measuring spot size: 20 ~ 21 mm

**Note (1) Definition of Viewing Angle :**




**Note (2) Definition of Contrast Ratio (CR):**

Measured at the center point of panel


Luminance with all pixels white

$$CR = \frac{\text{Luminance with all pixels white}}{\text{Luminance with all pixels black}}$$


**Note (3) Definition of Response Time: Sum of TR and TF**



**Note (4) Definition of optical measurement setup**



### Note (5) Definition of brightness uniformity



$$\text{Luminance uniformity} = \frac{(\text{Min Luminance of 9 points})}{(\text{Max Luminance of 9 points})} \times 100\%$$

## 4.0 INTERFACE PIN CONNECTION

### 4.1 Signal of interface

Terminal No.	Symbol	I/O	Functions
1--2	VLED+	P	Power for LED backlight (Anode)
3	VGH	P	Gate ON Voltage
4	VGL	P	Gate OFF Voltage
5	UPDN	I	Up/down selection
6	SHLR	I	Left / right selection
7--8	VLED-	P	Power for LED backlight (Cathode)
9	AVDD	P	Power for Analog Circuit
10	GND	P	Ground
11	MIPI_D3+	I	Positive MIPI differential data inputs3+
12	MIPI_D3-	I	Negative MIPI differential data inputs3-
13	GND	P	Ground
14	MIPI_D2+	I	Positive MIPI differential data inputs2+
15	MIPI_D2-	I	Negative MIPI differential data inputs2-
16	GND	P	Ground
17	MIPI_CLK+	I	Positive MIPI differential clock inputs+
18	MIPI_CLK-	I	Negative MIPI differential clock inputs-
19	GND	P	Ground
20	MIPI_D1+	I	Positive MIPI differential data inputs1+
21	MIPI_D1-	I	Negative MIPI differential data inputs1-
22	GND	P	Ground
23	MIPI_D0+	I	Positive MIPI differential data inputs0+
24	MIPI_D0-	I	Negative MIPI differential data inputs0-
25	GND	P	Ground
26	STBYB	I	Standby mode, normally pull high STBYB="1", normally operation STBYB="0", timing control, source driver will turn off
27	RESET	P	Global reset pin.
28	DVDD	P	Power for Digital Circuit
29	DVDD	P	Power for Digital Circuit
30	VCOM	P	Common voltage


## 5.0 FUNCTION DESCRIPTION

### 5.1.1 Power On/Off Sequence

In order to prevent IC from power on reset fail, the rising time (TPOR) of the digital power supply VDD should be maintained within the given specifications. Refer to “AC Characteristics” for more detail on timing. To prevent the device damage from latch up, the power on/off sequence shown below must be followed.



### 5.1.1 Enter and Exit Sleep Mode Sequence



Note: Low Level=3Fh, when NBW="L" (Normally white)  
Low Level=00h, when NBW="H" (Normally Black)

## 6.0 ELECTRICAL CHARACTERISTICS

### 6.1 TFT LCD Module

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	VDD	1.71	1.8	1.89	V
	VGH	17	18	19	V
	VGL	-7.5	-6.5	-5.5	V
	AVDD	9.4	9.6	9.8	V
VCOM	VCOM	3.0	(3.2)	3.5	V

Note:

(1) VGH is TFT Gate operating voltage.

(2) VGL is TFT Gate operating voltage. The low voltage level of VGH signal must be fluctuates with same phase as Vcom.

### 6.2 Back-Light Unit

The backlight system is an edge-lighting type with 27 LED.


The characteristics of the LED are shown in the following tables.

Item	Symbol	Min.	Typ.	Max.	Unit	Note
LED current	IL	-	180	-	mA	(2)
LED Voltage	VL	-	9.3	-	V	
Operating LED life time	Hr	20000	-	-	Hour	(1)(2)

Note (1) LED life time (Hr) can be defined as the time in which it continues to operate under the condition: Ta=25±3°C, typical IL value indicated in the above table until the brightness becomes less than 50%.

Note (2) The “LED life time” is defined as the module brightness decrease to 50% original brightness at Ta=25°C and IL=180mA. The LED lifetime could be decreased if operating IL is larger than 180mA. The constant current driving method is suggested.

LED CIRCUIT DIAGRAM: 3 x 9 = 27 LED



## 6.3 DC Characteristics


(VDD=VDD\_IF=1.8V, AVDD=8 to 13.5V, GND=AGND=GND\_IF=0V)


Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Low level input voltage	Vil	For the digital circuit	0	-	0.3×VDD	V
High level input voltage	Vih	For the digital circuit	0.7×VDD	-	VDD	V
Input leakage current	Ii	For the digital circuit	-	-	±1	µA
High level output voltage	Voh	Ioh= -400 µA	VDD- 0.4	-	-	V
Low level output voltage	Vol	Iol= +400 µA	-	-	GND+0.	V
Pull low/high resistor	Ri	For the digital input pin @	200K	250	300K	ohm
Digital Operation current	Idd	Fclk=51.2MHz, VDD=VDD_IF=1.8V	-	TB	-	mA
Digital Stand-by current	Ist1	Clock and all functions are stopped	-	10	50	µA
Analog Operating Current	Idda	No load, Fclk=51.2MHz, @AVDD=13.5V, V1=13.4V, V14=0.1V	-	10	12	mA
Analog Stand-by current	Ist2	No load, clock and all functions are stopped	-	10	50	µA
Input level of V1 ~ V7	Vref1	Gamma correction voltage input	0.4*AVDD	-	AVDD-	V
Input level of V8 ~ V14	Vref2	Gamma correction voltage input	0.1	-	0.6*AVD	V
Output Voltage deviation	Vod1	Vo = AGND+0.1V ~AGND+0.5V and Vo = AVDD-0.5V ~ AVDD-0.1V	-	±20	±35	mV
Output Voltage deviation	Vod2	Vo = AGND+0.5V ~ AVDD-0.5V	-	±15	±20	mV
Output Voltage Offset between Chips	Voc	Vo = AGND+0.5V ~ AVDD-0.5V	-	-	±20	mV
Dynamic Range of Output	Vdr	SO1 ~ 1536	0.1	-	AVDD-0.1	V
Sinking Current of Outputs	IOLy	SO1 ~ 1536; Vo=0.1V v.s 1.0V , AVDD=13.5V	80	-	-	uA
Driving Current of Outputs	IOHy	SO1 ~ 1536; Vo=13.4V v.s12.5V , AVDD=13.5V	80	-	-	uA
Resistance of Gamma Table	Rg	Rn: Internal gamma resistor	0.7*Rn	1.0*Rn	1.3*Rn	ohm

(VDD=VDD\_IF=1.8V, AVDD=8 to 13.5V, GND=AGND=GND\_IF=0V, TA=-20°C to 85°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit
MIPI Characteristics for High Speed Receiver					
Single-ended input low voltage(DSI-CLKP/N,DSI-DnP/N)	VILHS	-40	—	—	mV
Single-ended input high voltage (DSI-CLKP/N,DSI-DnP/N)	VIHHS	—	—	460	mV
Input Common-mode voltage (DSI-CLKP/N,DSI-DnP/N)	VCDRXDC	70	—	330	mV
Differential input impedance	ZID		100		ohm
HS transmit differential voltage(VOD=VDP-VDN)	VOD	140	200	250	mV
Low-level differential input voltage threshold	VTHLCLK VTHLDATA	-70	—	—	mV
High-level differential input voltage threshold	VTHHCLK VTHHDATA	—	—	—	mV
Single-ended threshold voltage for termination	VTERN_EN	—	—	450	mV
Termination capacitor	CTERM		—	14	pf

<b>Input voltage common mode variation(&lt;=450Mhz)</b>	VCMRCLK VCMRDATAL	-50	—	50	mV
<b>Input voltage common mode variation(&gt;=450Mhz)</b>	VCMRCLKM VCMRDATAM	—	—	100	mV
<b>MIPI Characteristics for Low Power Mode</b>					
<b>Pad signal voltage range</b>	<b>VI</b>	<b>-50</b>	—	<b>1350</b>	<b>mV</b>
<b>Ground shift</b>	<b>VGNDSH</b>	<b>-50</b>	—	<b>50</b>	<b>mV</b>
<b>Logic 0 input threshold</b>	<b>VIL</b>	<b>0</b>	—	<b>550</b>	<b>mV</b>
<b>Logic 1 input threshold</b>	<b>VIH</b>	<b>880</b>	—	<b>1350</b>	<b>mV</b>
<b>Logic 0 input voltage LPRX(CLK,ULP mode)</b>	<b>VILLPRXULP</b>	<b>0</b>	—	<b>300</b>	<b>mV</b>
<b>Input hysteresis</b>	<b>VHYST</b>	<b>25</b>	—	—	<b>mV</b>
<b>Output low level</b>	<b>VOL</b>	<b>-50</b>	—	<b>50</b>	<b>mV</b>
<b>Output high level</b>	<b>VOH</b>	<b>1.1</b>	<b>1.2</b>	<b>1.3</b>	<b>V</b>
<b>Output impedance of Low Power Transmitter</b>	<b>ZOLP</b>	<b>90</b>	<b>100</b>	<b>110</b>	<b>ohm</b>
<b>Logic 0 contention threshold</b>	<b>VILCD,MAX</b>	—	—	<b>200</b>	<b>mV</b>
<b>Logic 1 contention threshold</b>	<b>VIHCD,MIN</b>	<b>450</b>	—	<b>1350</b>	<b>mV</b>
<b>Logic high level input current</b>	<b>IIH</b>	—	—	<b>10</b>	<b>uA</b>
<b>Logic low level input current</b>	<b>III</b>	<b>-10</b>	—	—	<b>uA</b>
<b>Input pulse rejection (DSI-CLKP/N,DSI-DnP/N)</b>	<b>SGD</b>	—	—	<b>300</b>	<b>Vps</b>






## 6.4 AC Characteristics

### 6.4.1 Basic AC Characteristic

(VDD=VDD\_IF=1.8V, AVDD=8 to 13.5V, GND=AGND=GND\_IF=0V, TA=-20 to +85°C)


VDD/GRB AC characteristic

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
VDD power slew rate	TPOR	—	—	-20	ms	From 0 to 90% VDD
GRB active pulse width	TGRB	1	—	—	ms	VDD=VDD_IF=1.8V
VDD settle time	TRES	1	—	—	s	



3-wire interface AC characteristic:


Parameter	Symbol	Min.	Typ.	Max.	Unit
CSB falling to SCL rising	TSCL	200	-	-	ns
SCL pulse high period	TICWH	100	-	-	ns
SCL pulse low period	TICWL	100	-	-	ns
SCL pulse width	TICWP	250	-	-	ns
SDA data input setup time	TISU	100	-	-	ns
SDA data input hold time	TIHD	100	-	-	ns
SCL to CSB rising time	TISC	250	-	-	ns
CSB rising to failing time	TICD	1	-	-	us



#### 6.4.2 MIPI AC Characteristic


- LP Transmitter AC Specification

Parameter	Symbol	Min	Typ	Max	Units	Notes
15%~85% rising time and falling time	TRLP /TFLP	-	-	25	ns	-
30%~85% rising time and falling time	TREOT	-	-	35	ns	-
Pulse width of LP exclusive-OR	TLP-PULSE-TX	40	-	-	ns	-
First LP EXOR clock pulse after STOP state or Last pulse before stop state		20	-	-	ns	-
All other pulses		90	-	-	mV/ns	-
Period of the LP EXOR clock	TLP-PER-TX	30	-	500	mV/ns	-
Slew Rate @CLOAD =0pF	$\delta V/\delta t_{SR}$	30	-	200	mV/ns	-
Slew Rate @CLOAD =5pF		30	-	150	mV/ns	-
Slew Rate @CLOAD =20pF		30	-	100	mV/ns	-
Slew Rate @CLOAD =70pF		-	-	70	pF	-
Load Capacitance	TRLP	-	-	70	pF	-



### ● High Speed Transmission


Parameter	Symbol	Min	Typ	Max	Units
<b>UI instantaneous</b>	$UI_{INST}$	2	-	12.5	ns
<b>Data to Clock Skew(measured at transmitter)</b>	$T_{SKEW(TX)}$	-0.15	-	0.15	$UI_{INST}$
<b>Data to Clock Setup time(measured at receiver)</b>	$T_{SETUP(RX)}$	0.15	-	-	$UI_{INST}$
<b>Data to Clock Hold time(measured at receiver)</b>	$T_{HOLD(RX)}$	0.15	-	-	$UI_{INST}$
<b>20%~80% rise time and fall time</b>	$TR, TF$	150	-	-	ps
		-	-	0.3	$UI_{INST}$



### ● High Speed Clock Transmission


Parameter	Symbol	Min	Typ	Max	Units
Time that the transmitter shall continue sending HS clock after the last associated Data Lane has transitioned to LP mode	$T_{CLK-POST}$	$60+52UI$	-	-	ns
Detection time that the clock has stopped toggling	$T_{CLK-MISS}$	-	-	60	ns
Time to drive LP-00 to prepare for HS clock transmission	$T_{CLK-PREPARE}$	38	-	95	ns

<b>Minimum lead HS-0 drive period before starting clock</b>	TCLK-PREPARE + TCLK-ZERO	300	-	-	ns
<b>Time to enable Clock Lane receiver line termination measured from when Dn cross VIL,MAX</b>	THS-TERM-EN	-	-	38	ns
<b>Minimum time that the HS clock must be prior to any associated data lane beginning the transmission from LP to HS mode</b>	TCLK-PRE	8	-	-	UI
<b>Time to drive HS differential state after last payload clock bit of a HS transmission burst</b>	TCLK-TRAIL	60	-	-	ns



### ● Bursts Mode Data Transmission

Parameter	Symbol	Min	Typ	Max	Units
Time to drive LP-00 to prepare for HS transmission	THS-PREPARE	40+4UI	-	85+6UI	ns
Time from start of $t_{HS-TRAIL}$ or $t_{CLK-TRAIL}$ period to start of LP-11 state	TEOT	-	-	105+12UI	ns
Time to enable Data Lane receiver line termination measured from when Dn cross VIL,MAX	THS-TERM-EN	-	-	35+4UI	ns
Time to drive flipped differential state after last payload data bit of a HS transmission burst	THS-TRAIL	60+4UI	-	-	ns
Time-out at RX to ignore transition period of EoT	THS-SKIP	40	-	55+4UI	ns
Time to drive LP-11 after HS burst	THS-EXIT	100	-	-	ns
Length of any Low-Power state period	TLPX	50	-	-	ns
Sync sequence period	THS-SYNC	-	8UI	-	ns
Minimum lead HS-0 drive period before the Sync sequence	THS-ZERO	105+6UI	-	-	ns



#### 6.4.3 Input Timing for MIPI

HV mode

Vertical input timing

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Vertical display area	tvd		600		H
VSYNC period time	tv	624	635	800	H
VSYNC pulse width	tvpw	1	—	20	H
VSYNC back porch	tvb	23	23	23	H
VSYNC front porch	tvfp	1	12	177	H

HV mode

Horizontal input timing

Parameter	Symbol	Value			Unit	
Horizontal display area	thd	1024			DCLK	
DCLK frequency@ Frame rate=60hz	fclk	Min.	Typ.	Max.	Mhz	
		44.9	51.2	70.3		
1 Horizontal Line	th	1200	1344	1464	DCLK	
HSYNC pulse width	thpw	Min.	1			
		Typ.	—			
		Max.	140			
HSYNC blanking	thb	160	160	160		
HSYNC front porch	thfp	16	160	216		

## 7.0 Reliability test items

Test Item	Test Conditions	Notes
High temperature Operation	Ta= +70°C , 120hrs	
Low temperature Operation	Ta= -20°C , 120hrs	
High Temperature Storage	Ta= +80°C , 120hrs	
Low Temperature Storage	Ta= -30°C , 120hrs	
Humidity Test	60°C ,Humidity 90% ,96hrs	
Thermal Shock Test	-20°C ,30min~+70°C ,30min (30 cycle)	
Vibration Test(Packing)	Sine Wave 1.04G, 5~500Hz, XYZ 30min/each direction	
Static Electricity	Half-Sine, 100G, 6ms, ±XYZ, 3 cycle	

## 8.0 OUTLINE DIMENSION

1	2	3	4	5	6																																																																																								
客户 For Customer:	客户料号 :	客户版本 :	REV&EIT	DESCRIPTIONS 内容	REV&EIT 者 DATE 打印日期																																																																																								
	承认签名 :	承认日期 :																																																																																											
<b>A</b>																																																																																													
<b>B</b>																																																																																													
<b>C</b>																																																																																													
<p>Notes:</p> <p>1. LED CIRCUIT DIAGRAM:</p> <p>2. ROHS must be complied.</p> <p>3. LCD IC: K79001H-K79323HGC</p> <p>4. POL: 上偏振(50°) 下光轴(0°) TPS/H</p> <p>4. DISPLAY TYPE: 0 BOE TFT/IPS;</p> <p>5. All radii without dimension RO3. Unspecified Tolerances is: <math>\pm 0.2</math></p> <p><b>E lectrical-Optical Characteristics (<math>T_a=25^\circ C</math>):</b></p> <table border="1"> <thead> <tr> <th>Item (项目)</th> <th>Symbol (符号)</th> <th>Symbol (符号)</th> <th>min. (最小)</th> <th>typ. (典型)</th> <th>max. (最大)</th> <th>Unit (单位)</th> <th>Condition/测定条件</th> </tr> </thead> <tbody> <tr> <td>Main Uni form ity (均匀度)</td> <td>L<sub>V</sub></td> <td>260 (透屏) 280 (透屏)</td> <td></td> <td></td> <td>%</td> <td>cd/m<sup>2</sup></td> <td>I<sub>f</sub>=180 mA (恒定电流测试)</td> </tr> <tr> <td>SubZer uni form ity (均匀度)</td> <td>Avg</td> <td>90</td> <td>95</td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>SubZen uni form ity (均匀度)</td> <td>Colour (色度坐标)</td> <td>X</td> <td>0.3</td> <td>0.32</td> <td></td> <td></td> <td></td> </tr> <tr> <td>SubZen uni form ity (均匀度)</td> <td>Coordinate</td> <td>Y</td> <td>0.3</td> <td>0.32</td> <td></td> <td>cd/m<sup>2</sup></td> <td>MeasRZ tolerance:</td> </tr> <tr> <td>SubZen uni form ity (均匀度)</td> <td>Luminance (亮度)</td> <td>L<sub>V</sub></td> <td>—</td> <td>—</td> <td>—</td> <td>%</td> <td>Luminance: <math>\pm 5\%</math></td> </tr> <tr> <td>SubZen uni form ity (均匀度)</td> <td>Avg</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>%</td> <td>Colour coordinate: <math>\pm 0.008</math></td> </tr> <tr> <td>Forward Voltage (正向电压)</td> <td>V<sub>f</sub></td> <td>8.8</td> <td>9.3</td> <td>9.5</td> <td>V</td> <td>mA</td> <td>Voltage: <math>\pm 0.1V</math></td> </tr> <tr> <td>Reverse Current (反向电流)</td> <td>I<sub>r</sub></td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td>—</td> <td></td> </tr> <tr> <td>Operating Temperature</td> <td>(工作温度)</td> <td>20~+60 °C</td> <td>• Storage Temperature</td> <td>RZ (贮存温度)</td> <td>30~+70 °C</td> <td></td> <td></td> </tr> <tr> <td>Storage condition Recommended:</td> <td></td> <td>temperature RZ (25~G±5 °C)</td> <td>and humidity (65%RH±20%RH)</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						Item (项目)	Symbol (符号)	Symbol (符号)	min. (最小)	typ. (典型)	max. (最大)	Unit (单位)	Condition/测定条件	Main Uni form ity (均匀度)	L <sub>V</sub>	260 (透屏) 280 (透屏)			%	cd/m <sup>2</sup>	I <sub>f</sub> =180 mA (恒定电流测试)	SubZer uni form ity (均匀度)	Avg	90	95					SubZen uni form ity (均匀度)	Colour (色度坐标)	X	0.3	0.32				SubZen uni form ity (均匀度)	Coordinate	Y	0.3	0.32		cd/m <sup>2</sup>	MeasRZ tolerance:	SubZen uni form ity (均匀度)	Luminance (亮度)	L <sub>V</sub>	—	—	—	%	Luminance: $\pm 5\%$	SubZen uni form ity (均匀度)	Avg	—	—	—	—	%	Colour coordinate: $\pm 0.008$	Forward Voltage (正向电压)	V <sub>f</sub>	8.8	9.3	9.5	V	mA	Voltage: $\pm 0.1V$	Reverse Current (反向电流)	I <sub>r</sub>	—	—	—	—	—		Operating Temperature	(工作温度)	20~+60 °C	• Storage Temperature	RZ (贮存温度)	30~+70 °C			Storage condition Recommended:		temperature RZ (25~G±5 °C)	and humidity (65%RH±20%RH)				
Item (项目)	Symbol (符号)	Symbol (符号)	min. (最小)	typ. (典型)	max. (最大)	Unit (单位)	Condition/测定条件																																																																																						
Main Uni form ity (均匀度)	L <sub>V</sub>	260 (透屏) 280 (透屏)			%	cd/m <sup>2</sup>	I <sub>f</sub> =180 mA (恒定电流测试)																																																																																						
SubZer uni form ity (均匀度)	Avg	90	95																																																																																										
SubZen uni form ity (均匀度)	Colour (色度坐标)	X	0.3	0.32																																																																																									
SubZen uni form ity (均匀度)	Coordinate	Y	0.3	0.32		cd/m <sup>2</sup>	MeasRZ tolerance:																																																																																						
SubZen uni form ity (均匀度)	Luminance (亮度)	L <sub>V</sub>	—	—	—	%	Luminance: $\pm 5\%$																																																																																						
SubZen uni form ity (均匀度)	Avg	—	—	—	—	%	Colour coordinate: $\pm 0.008$																																																																																						
Forward Voltage (正向电压)	V <sub>f</sub>	8.8	9.3	9.5	V	mA	Voltage: $\pm 0.1V$																																																																																						
Reverse Current (反向电流)	I <sub>r</sub>	—	—	—	—	—																																																																																							
Operating Temperature	(工作温度)	20~+60 °C	• Storage Temperature	RZ (贮存温度)	30~+70 °C																																																																																								
Storage condition Recommended:		temperature RZ (25~G±5 °C)	and humidity (65%RH±20%RH)																																																																																										
<b>D</b>																																																																																													
<table border="1"> <thead> <tr> <th>Model No. : HC0701K28026-B62</th> <th>Drawing No. : 汇益鑫型号: HC0701K28026-B62</th> </tr> </thead> <tbody> <tr> <td>Drawing No. : 汇益鑫图号: HC0701K28026-B62</td> <td>Model No. : 汇益鑫型号: HC0701K28026-B62</td> </tr> <tr> <td>UNIT (单位) mm</td> <td>THE THIRD ANGLE PROJECTION</td> </tr> <tr> <td>DESIGN 设计:</td> <td>EDITION 版本号: A/1</td> </tr> <tr> <td>CHECKED 审核:</td> <td>DATE 日期:</td> </tr> <tr> <td>APPROVED 批准:</td> <td>DATE 日期:</td> </tr> </tbody> </table>						Model No. : HC0701K28026-B62	Drawing No. : 汇益鑫型号: HC0701K28026-B62	Drawing No. : 汇益鑫图号: HC0701K28026-B62	Model No. : 汇益鑫型号: HC0701K28026-B62	UNIT (单位) mm	THE THIRD ANGLE PROJECTION	DESIGN 设计:	EDITION 版本号: A/1	CHECKED 审核:	DATE 日期:	APPROVED 批准:	DATE 日期:																																																																												
Model No. : HC0701K28026-B62	Drawing No. : 汇益鑫型号: HC0701K28026-B62																																																																																												
Drawing No. : 汇益鑫图号: HC0701K28026-B62	Model No. : 汇益鑫型号: HC0701K28026-B62																																																																																												
UNIT (单位) mm	THE THIRD ANGLE PROJECTION																																																																																												
DESIGN 设计:	EDITION 版本号: A/1																																																																																												
CHECKED 审核:	DATE 日期:																																																																																												
APPROVED 批准:	DATE 日期:																																																																																												
<b>Hetech</b>																																																																																													
1	2	3	4	5	6																																																																																								

## **9.0 General precaution**

### **9.1 Use Restriction**

This product is not authorized for use in life supporting systems, aircraft navigation control systems, military systems and any other application where performance failure could be life threatening or otherwise catastrophic.

### **9.2 Disassembling or Modification**

Do not disassemble or modify the module. It may damage sensitive parts inside LCD module, and may cause scratches or dust on the display. HC does not warrant the module, if customers disassemble or modify the module.

### **9.3 Breakage of LCD Panel**

9.3.1. If LCD panel is broken and liquid crystal spills out, do not ingest or inhale liquid crystal, and do not contact liquid crystal with skin.

9.3.2. If liquid crystal contacts mouth or eyes, rinse out with water immediately.

9.3.3. If liquid crystal contacts skin or cloths, wash it off immediately with alcohol and rinse thoroughly with water.

9.3.4. Handle carefully with chips of glass that may cause injury, when the glass is broken.

### **9.4 Electric Shock**

9.4.1. Disconnect power supply before handling LCD module.

9.4.2. Do not pull or fold the LED cable.

9.4.3. Do not touch the parts inside LCD modules and the fluorescent LED's connector or cables in order to prevent electric shock.

### **9.5 Absolute Maximum Ratings and Power Protection Circuit**

9.5.1. Do not exceed the absolute maximum rating values, such as the supply voltage variation, input voltage variation, variation in parts' parameters, environmental temperature, etc., otherwise LCD module may be damaged.

9.5.2. Please do not leave LCD module in the environment of high humidity and high temperature for a long time.

9.5.3. It's recommended to employ protection circuit for power supply.

### **9.6 Operation**

9.6.1 Do not touch, push or rub the polarizer with anything harder than HB pencil lead.

9.6.2 Use finger stalls of soft gloves in order to keep clean display quality, when persons handle the LCD module for incoming inspection or assembly.

9.6.3 When the surface is dusty, please wipe gently with absorbent cotton or other soft material.

9.6.4 Wipe off saliva or water drops as soon as possible. If saliva or water drops contact with polarizer for a long time, they may causes deformation or color fading.

9.6.5 When cleaning the adhesives, please use absorbent cotton wetted with a little petroleum benzine or other adequate solvent.

### **9.7 Mechanism**

Please mount LCD module by using mouting holes arranged in four corners tightly.

### **9.8 Static Electricity**

9.8.1 Protection film must remove very slowly from the surface of LCD module to prevent from electrostatic occurrence.

9.8.2. Because LCD module use CMOS-IC on circuit board and TFT-LCD panel, it is very weak to electrostatic discharge. Please be careful with electrostatic discharge. Persons who handle the module should be grounded through adequate methods.

### **9.9 Strong Light Exposure**

The module shall not be exposed under strong light such as direct sunlight. Otherwise, display characteristics may be changed.

### **9.10 Disposal**

When disposing LCD module, obey the local environmental regulations.